



## Lifeloc EASYCAL<sup>®</sup> G2 Automatic Calibration Station

The EASYCAL G2 is the next generation in workplace alcohol breath testing compliance. The G2 Automates every step of EBT calibration and checks with its ID enabled tanks and simplified process.

From start to finish—just cradle your EBT, power on and the EASYCAL G2 does the rest.

# Lifeloc

Professional Breath Alcohol Tester



**remedyNOW Consulting, LLC**

4432 N 109th Street • Wauwatosa • WI • 53225  
414-858-8014 • [www.remedynewconsulting.com](http://www.remedynewconsulting.com)



## Lifeloc EASYCAL<sup>®</sup> G2

### Fast and Simple to Use

- One-touch calibration and calibration checks
- Large color touchscreen for easy navigation
- Reduces gas usage
- Significantly faster calibrations than the competition
- Displays date, time, and power status
- Calibration and cal-check progress bar
- Allows for up to 100 individual operators

### Compliance Management Features

- Utilizes ID enabled tanks that automatically read and store tank value, expiration date and lot code
- Cylinder Expiry Lockout prevents the use of expired gas
- Low Gas Alert Warns of low gas volume and shows percent of tank remaining
- Calibration Warning helps prevent an inadvertent calibration after a positive test
- Auto Altitude Correction
- Security allows you to assign, enable or disable users and passwords
- Sequence Software ensures all cal/cal-checks are performed and documented correctly
- Serial Numbers are read and stored with each event
- Print Log stores all cal/cal-checks across unlimited EBTs

Display	Full Color Digital LCD Resistive Touchscreen
Cylinder Size	Accommodates 34L, 60L, 105L and 116L gas cylinders
Available Gas Standards	0.040, 0.080, 0.100**
EBT Seat Sensor	Ensures Proper Device Seating
Cylinder Pressure Sensor	Automatically checks tank volume
Barometric Pressure Sensor	Automatically Corrects Altitude
Recovery Time	Immediate
Calibration Time	< 2 minutes
Calibration Check Time	< 30 seconds
Operating Temperature Range	50° - 113° F (10° - 45° C)
User Selectable Power Options	9VDC 3A Regulated 6 C Alkaline Auto Sleep Mode
Power Save Feature	Auto Shutoff
Dimensions	Approx. 10.6" L x 9.25" W x 5.3" H (270 x 235 x 135 mm)
Weight	3 Pounds (48 ounces, 1360 grams)
Printer Communication Standard	Bluetooth
Software Updates	Field updatability via USB
Memory	Approx. 10,000 records before overwriting
Unit of Measure	BAC Standard International UOM Available
Language	English Standard Additional Languages Available.
Date/Time	User Selectable International Date and Time Formats
Certifications	CE
Housing	Ruggedized ABS Plastic
Warranty	2 year Limited Parts and Labor

**remedyNOW Consulting, LLC**

4432 N 109th Street • Wauwatosa • WI • 53225

414-858-8014 • [www.remedynowconsulting.com](http://www.remedynowconsulting.com)